AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

- (Original) A system that refines a general-purpose search engine, comprising:

 a component that identifies an entry point to the general-purpose search engine;

 and
- a tuning component that filters search query results of the general-purpose search engine based on criteria associated with the entry point.
- 2. (Original) The system of claim 1, the criteria comprising one or more of a document property, a context parameter, and a configuration.
- 3. (Original) The system of claim 2, the document property comprising one or more of a term that appears on a web page, a property of a Uniform Resource Locator (URL) identifying the web page, a property of a plurality of URLs that link to the web page, a property of a plurality of web pages that link to the web page, and a layout.
- 4. (Original) The system of claim 2, the context parameter comprising one of a word probability and a probability distribution
- 5. (Original) The system of claim 1, the tuning component provided with training data to learn what properties of a document are indicative of the document being relevant to a user executing a search query from the entry point.
- 6. (Original) The system of claim 1, the tuning component configured to differentiate between a query result that is relevant to a search query context for a group of users and a query result that is non-relevant to the search query context for the group of users.

- 7. (Currently amended) The system of claim 1, the tuning component <u>employs</u> configured to employ statistical analysis in connection with filtering the search query results.
- 8. (Currently amended) The system of claim 1, the tuning component generates employed to generate one or more context parameters for a received query result, and compares then compare the generated context parameters with a relevant context parameter and a non-relevant context parameter to determine whether the query result is relevant.
- 9. (Currently amended) The system of claim 1, the tuning component further <u>ranks</u> employed to rank the query results.
- 10. (Currently amended) The system of claim 9, the ranking determined by the degree of relevance of the query result to a relevant data set and a non-relevant data set, wherein the relevance is determined via one of a similarity measure and a confidence interval.
- 11. (Original) The system of claim 9, the ranking order comprising one of ascending and descending, from the most relevant result to the least relevant result.
- 12. (Original) The system of claim 1, the tuning component configured for a plurality of entry points associated with one or more groups of users.
- 13. (Currently amended) A system that tunes a general-purpose search engine, comprising:
- a filter component that parses relevant and non-relevant general-purpose search engine content results for an entry point <u>leading to the general-purpose search engine</u> based on training data; and
- a ranking component that sorts the filtered results in accordance with the training data for presentation to a user.

- 14. (Currently amended) The system of claim 13, the filter component <u>parses</u> parsing the results as a function of one or more of a document property, a context parameter, and a configuration associated with the entry point.
- 15. (Original) The system of claim 13, the filter component trained to differentiate between a relevant and a non-relevant result *via* the training data.
- 16. (Currently amended) The method of claim 13, the training data comprising a set of relevant data associated with a search context of a user for the entry point and a set [[et]] of non-relevant data comprising random data unrelated to the search context of the user for the entry point.
- 17. (Currently amended) The system of claim 13, the filter component employs configured to omploy statistical analysis to determine facilitate determining whether a result is relevant or non-relevant to the entry point.
- 18. (Currently amended) The system of claim 13, the ranking component employs employing a technique to determine the degree of relevance of the query results with respect to a relevant data set and a non-relevant data set.
- 19. (Original) The system of claim 18, the technique comprising one of a similarity measure and a confidence interval.
- 20. (Original) The system of claim 13, the ranking order comprising one of ascending and descending, from the most relevant result to the least relevant result.
- 21. (Currently amended) The system of claim 18, the ranking performed on the relevant query results, wherein the non-relevant results are discarded.

- 22. (Currently amended) A method to filter and rank general-purpose search engine results associated with an entry point, comprising:
- executing a query search with the general-purpose search engine through the entry point;

filtering the general-purpose search engine results by tuning the general-purpose search engine for the entry point; and

ranking the general-purpose search engine results.

- 23. (Original) The method of claim 22, further comprising employing a statistical hypothesis to determine whether a result is relevant or non-relevant to a search context of the entry point.
- 24. (Currently amended) The method of claim 23, the statistical hypothesis employing a threshold in connection with a probability distribution for relevant data and a probability distribution for non-relevant data, wherein respective word probabilities are generated for the search query results and compared to the threshold, the probability distribution for relevant data and the probability distribution for non-relevant data to determine whether the results are relevant or non-relevant.
- 25. (Original) The method of claim 24, the threshold employed to bias the decision to mitigate one of a result being deemed non-relevant when the result is relevant and a result being deemed relevant when the result is non-relevant.
- 26. (Original) The method of claim 22, further employing a probability distribution analysis or machine learning in connection with the filtering and ranking, wherein suitable probability distributions include a Bernoulli, a binomial, a Pascal, a Poisson, an arcsine, a beta, a Cauchy, a chi-square with N degrees of freedom, an Erlang, a uniform, an exponential, a gamma, a Gaussian-univariate, a Gaussian-bivariate, a Laplace, a lognormal, a rice, a Weibull and a Rayleigh distribution, and the machine learning can classify based on one or more of a word occurrence, a distribution, a page layout, an inlink, and an outlink.

- 27. (Original) The method of claim 22, further comprising employing a statistical analysis to rank search query results.
- 28. (Original) The method of claim 27, the ranking comprising one of generating word probabilities and employing a confidence interval to determine relevance, and generating a similarity measure comprising one of a cosine distance, the Jaccard coefficient, an entropy-based measure, a divergence measure and/or a relative separation measure to determine similarity.
- 29. (Currently amended) A method to manually customize a general-purpose search engine for an entry point, comprising:

providing a set of relevant data to train a component to discern query results relevant to a search context of a user employing the entry point, the entry point being a gateway to the general-purpose search engine; [[and]]

providing a set of non-relevant data to train the component to discern query results unrelated to the search context, wherein the set of relevant data and the set of non-relevant data are manually provided; and

determining and then employed to determine whether a query result is relevant to the search context based on the set of relevant data and the set of non-relevant data.

- 30. (Original) The method of claim 29, the set of relevant data comprising data associated with the search context of the user for the entry point.
- 31. (Original) The method of claim 29, the set of non-relevant data comprising random data unrelated to the search context of the user for the entry point.
- 32. (Original) The method of claim 29, further comprising providing information to associate respective query results with the entry point.

- 33. (Original) The method of claim 29, the set of relevant data and the set of non-relevant data employed to train the component to learn the features that differentiate relevant data from non-relevant data.
- 34. (Currently amended) A method to automatically customize a general-purpose search engine for an entry point, comprising:

executing a query search via the entry point that routes to the general-purpose search engine;

recording a query result selected by a user as relevant;

recording a higher ranked query results, wherein a lower ranked result is selected by the user, as non-relevant; and

providing the recorded results to automatically train the filter to discriminate between results relevant to a search context of the user for the entry point and results non-relevant to the search context.

- 35. (Original) The method of claim 34, the set of relevant data comprising data associated with the search context of the user for the entry point.
- 36. (Original) The method of claim 34, the set of non-relevant data comprising data unrelated to the search context of the user for the entry point.
- 37. (Original) The method of claim 34, further comprising providing information to associate respective query results with the entry point.
- 38. (Original) The method of claim 34, the set of relevant data and the set of non-relevant data employed to train the component to learn the features that differentiate relevant data from non-relevant data.
- 39. (Currently amended) The method of claim 34, the query results selected *via* a click thru technique employing, wherein a mouse is employed to select a link associated with the query result by clicking on the link.

40. (Original) The method of claim 34, further comprising generating a word probability distribution for the relevant recorded results and a word probability distribution for the non-relevant recorded results.

41. (Canceled).

42. (Currently amended) A computer readable medium storing computer executable components that tunes a general-purpose search engine to improve context search query results, comprising:

a component that filters the general-purpose search engine results based on training data sets associated with the search context of a user for an entry point to the general-purpose search engine; and

a component that ranks the general-purpose search engine results according to the similarity of the search engine results to the training data sets.

43. (Currently amended) A system that filters and ranks general-purpose search engine results, comprising:

means for filtering general-purpose search engine results to determine whether a query result is relevant to a search context of a group of users and an entry point <u>leading</u> to the general-purpose search engine; [[,]] and

means for ranking the general-purpose search engine results based on a relevance of the general-purpose search engine results to the search context of a group of users and an entry point.